

項目		単位	記号	寸 法									
タイロッドの呼称			dT	50	55	60	65	70	75	80	85	90	
タイロッド本体	ネジ部呼び径		S <sub>T</sub>	M48	M52	M60	M64	M68	M72	M80	M85	M90	
	ネジ切長さ	mm	ℓ <sub>T</sub>	160	160	170	170	170	180	180	180	180	
	棒径部m当り重量	kg/m		15.4	18.7	22.2	26.0	30.2	34.7	39.5	44.5	49.9	
ターンバツクル	外 径	mm	d <sub>0</sub>	85	90	110	120	120	120	140	140	150	
				80	85	100	110	110	110	130	140	150	
	内 径	mm	d <sub>1</sub>	51	55	63	67	71	75	83	88	93	
				51	55	63	67	71	75	83	88	93	
	全 長	mm	L <sub>0</sub>	350	370	390	400	400	420	420	420	420	
				350	370	390	400	400	420	420	420	420	
	孔 径	mm	d	20	25	25	30	30	30	30	30	30	30
				20	25	25	30	30	30	30	30	30	
	ネジ切長さ	mm	L <sub>1</sub>	60	70	80	80	80	90	90	90	90	100
				50	60	65	70	75	75	80	90	95	
	ネジ呼径		S <sub>T</sub>	M48	M52	M60	M64	M68	M72	M80	M85	M90	
				M48	M52	M60	M64	M68	M72	M80	M85	M90	
	重 量	kg		10.1	11.9	20.1	25.0	23.7	23.5	33.7	31.6	37.0	
				8.5	9.6	14.9	19.2	17.9	19.4	26.7	31.7	36.9	
定着ナット	呼 び 径		S <sub>T</sub>	M48	M52	M60	M64	M68	M72	M80	M85	M90	
				M48	M52	M60	M64	M68	M72	M80	M85	M90	
	高 さ	mm	H	48	52	60	64	68	72	80	85	90	
				48	52	60	64	68	72	80	85	90	
	対 辺 距 離	mm	B	75	80	90	95	100	105	115	120	130	
				75	80	90	95	100	105	115	120	130	
	重 量	kg		1.24	1.49	2.11	2.50	2.87	3.32	4.31	4.84	6.19	
				1.24	1.49	2.11	2.50	2.87	3.32	4.31	4.84	6.19	