

ネジ部の基準寸法と有効断面積

	ネジの呼び	ピッチ mm	雄ネジ			有効断面積 mm ²
			外径	有効径	谷径	
			mm	mm	mm	
一般用メートルネジ	M 24	3	24	22.051	20.752	352.5
	M 27	3	27	25.051	23.752	459.4
	M 30	3.5	30	27.727	26.211	560.6
	M 33	3.5	33	30.727	29.211	693.6
	M 36	4	36	33.402	31.67	816.7
	M 39	4	39	36.402	34.67	975.8
	M 42	4.5	42	39.077	37.129	1121
	M 45	4.5	45	42.077	40.129	1306
	M 48	5	48	44.752	42.587	1473
	M 52	5	52	48.752	46.587	1758
	M 56	5.5	56	52.428	50.046	2030
	M 60	5.5	60	56.428	54.046	2362
	M 64	6	64	60.103	57.505	2676
	M 68	6	68	64.103	61.505	3055
	M 72	6	72	68.103	65.505	3460
	M 76	6	76	72.103	69.505	3889
	M 80	6	80	76.103	73.505	4344
	M 85	6	85	81.103	78.505	4948
	M 90	6	90	86.103	83.505	5591
	M 95	6	95	91.103	88.505	6273
M 100	6	100	96.103	93.505	6995	

※ ネジの基準寸法は、JIS B 0205 一般用メートルネジによります